

Recycled Content: up to 82%

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views
✓	✓	✓	✓	✓	✓
Location Dependent					

LEED for Schools

Acoustics	Low Emitting or CHPS
✓	✓



Acoustic Ceiling Tile Specifications



9/16" Exposed Tee grid



9/16" Dimensional Tee grid

Sizes up to 50,000 sq ft using a single image

Key Selection Attributes



- Smooth, clean, durable finish – Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- Scrubbable and water-repellent
- Excellent sound absorption
- High recycled content options
 - pre-consumer, 15% post-consumer
- 30-Year Limited System Warranty against visible sag and bacterial growth
- Non-directional visual reduces installation time and scrap
- Smaller size panels available (1 carton min. order).
- Excellent sound blocking – Plank sizes available.
- Meets USDA/FSIS guidelines for use in food processing areas

Typical Applications

- Offices
- Healthcare – assists in addressing HIPAA requirements
- Classrooms
- Corridors
- Lobbies/reception areas
- Department stores/retail
- Kitchens, dining rooms, and food preparation areas

Visual Selection

Performance Selection

Dots represent highest level of performance.

Edge Profile	Item No.	Dimensions	UL Classified	Acoustics	Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	VOC Formaldehyde	Durable	Recycle Program
				NRC	CAC						
		2' x 2' x 3/4"		0.60	40	Class A	0.90	•	No Added	•	•
		600 x 600 x 19mm		•	•	•	•	•	•	•	•
		2' x 4' x 3/4"		0.70	35	Class A	0.90	•	No Added	•	•
		600 x 1200 x 19mm		•	•	•	•	•	•	•	•
		2' x 4' x 3/4"		•	•	•	•	•	•	•	•

Available in Edge:
Square Lay-in
& Tegalur
2'x2' (600x600)
2'x4' (600x1200)
4'x4' (1200x1200)

Please contact www.ArtificialSky.com email Sales@ArtificialSky.com for any questions or additional information. Thank you.